

BF64WW | WINDOW WALL SYSTEMS

TECHNICAL DATA



With its wide range scope of design applications BF64WW window wall system offers following features:

STANDARD FEATURES

- 2-1/2" frame depth
- Receptor system
- 1/16" wall thickness
- Thermally broken aluminum profiles
- Powder coating with all standard RAL colors and various anodized colors
- Qualicoat & Qualanod certified surface treatment applications.

OPTIONAL FEATURES

- 3/32" wall thickness
- Powder coated dual finish (two-tone color) option
- High insulated profile system for better energy efficiency
- Up to 1-1/2" Insulated glass with low-e or solar low-e options
- Warmedge spacer and triple IGU to maximize energy efficiency
- Sound insulated profile system for superior OITC ratings
- Bird friendly glazing
- Integrated slab cover



PERFORMANCE VALUES

Air infiltration	<0.1 cfm/ft ² @ 6.24 psf
Water penetration	15 psf
Wind resistance design	75 psf
Wind resistance overload	112 psf
U-Value	0.37 - 0.48 Btu/(h.ft ² .°F)

PERFORMANCE TEST STANDARTS

Air infiltration	ASTM E283
Water penetration	ASTM E331
Structural - Uniform Wind Load	ASTM E330
Thermal transmittance U-Factor	NFRC100, 102, 500; AAMA 1503
Solar Heat Gain Cefficient (SHGC)	NFRC 200
Visible Sound Transmission (STC, OITC)	ASTM E90

